

# SOLiVi4 15 TL

PRELIMINARY



# 15 kW transformer-less solar inverter

**SOLIVIA** - The new generation of solar inverters from Delta offer high-efficiency string and central inverters. SOLIVIA stands for *Solar inverters for versatile and intelligent applications*.



## One model for all countries

One unit can be used in more than eight European countries (e. g. DE, IT, ES, FR, CZ, BE, GR, PT, etc.) simply by the click of a button! The multi-country models will help Delta and our customers to save costs in production, warehousing and logistics.



## Temperature & design improvements

The SOLIVIA solar inverters from Delta are dust tight (IP54/IP65) and operate over a wide range of temperatures. A very high efficiency of 98.0 %, a wide input voltage range of 200 up to 1000 V as well as 2 MPP trackers give you ultimate flexibility when designing your system.



## State-of-the-art display

The user-friendly menu navigation via the integrated black/white graphical LCD display makes the unit easy to operate. The user interface offers a choice of 5 different languages (DE, EN, IT, ES, FR).



## Simple handling

The SOLIVIA 15 TL inverters have an integrated DC disconnecter that saves our customers installation costs and the cost of an external DC disconnecter.

INPUT (DC)	
Max. recommended PV power	19.0 kW
Nominal power	16.5 kW
Nominal voltage	630 V
Voltage range	200 ... 1000 V
MPP range	350 ... 800 V
No. of MPP trackers	2
Max. current	46 A (23 A x 2)

OUTPUT (AC)	
Max. power	16.0 kW
Nominal power	15.0 kW
Voltage range (3 phase, 3 wire) *	3 x 400 V (-20 % / +20 %)
Nominal current	22 A
Max. current	25 A
Nominal frequency	50 / 60 Hz
Frequency range *	50 Hz: 47.0 ... 53.0 Hz 60 Hz: 57.0 ... 63.0 Hz
Power factor	> 0.99 @ nominal power

GENERAL SPECIFICATION	
Model name	SOLIVIA 15 EU G3 TL
Max. efficiency	98.0 %
Efficiency EU	> 97.5 %
Operating temperature	-20 ... +60 °C
Storage temperature	-20 ... +80 °C
Humidity	0 ... 90 %

STANDARDS	
Protection degree	IP54 / IP65
Safety class	1
Configurable trip parameters	Yes
Insulation monitoring	Yes
Anti-islanding protection	VDE 0126-1-1; RD 1663; DK 5940 Ed. 2.2;
	EN 50438

MECHANICAL DESIGN	
Size (L x W x D)	952.0 x 624.7 x 278.0 mm
Weight	63.0 kg
Cooling	Fan
AC connector	Wieland RST50i5
DC connector	4 pairs Multicontact MC4
Communication	2 RJ45 / RS485
Display	Black/white graphical LCD
DC disconnecter	Integrated

DIRECTIVES	
EMC	EN61000-6-2; EN61000-6-3 EN61000-3-11; EN61000-3-12
Safety	EN60950-1; EN50178; IEC62103; IEC62109-1 / -2

\* AC voltage and frequency range will be programmed according to the individual country requirements. AC output is Delta grid without neutral.

Delta Energy Systems (Germany) GmbH

Tscheulinstrasse 21

D-79331 Teningen

Germany

Email: [sales@solar-inverter.com](mailto:sales@solar-inverter.com)

Sales Hotline: 0180 10 SOLAR (76527)

Mondays to Fridays from 8 am to 5 pm (apart from official Bank Holidays) (3,9 ct/min)

[www.solar-inverter.com](http://www.solar-inverter.com)

[www.secondlife.solar-inverter.com](http://www.secondlife.solar-inverter.com)

19 March 2010



# SOLiVi4 20 TL

PRELIMINARY



# 20 kW transformer-less solar inverter

**SOLIVIA** - The new generation of solar inverters from Delta offer high-efficiency string and central inverters. SOLIVIA stands for *Solar inverters for versatile and intelligent applications*.



## One model for all countries

One unit can be used in more than eight European countries (e. g. DE, IT, ES, FR, CZ, BE, GR, PT, etc.) simply by the click of a button! The multi-country models will help Delta and our customers to save costs in production, warehousing and logistics.



## Temperature & design improvements

The SOLIVIA solar inverters from Delta are dust tight (IP54/IP65) and operate over a wide range of temperatures. A very high efficiency of 98.1 %, a wide input voltage range of 200 up to 1000 V as well as 2 MPP trackers give you ultimate flexibility when designing your system.



## State-of-the-art display

The user-friendly menu navigation via the integrated black/white graphical LCD display makes the unit easy to operate. The user interface offers a choice of 5 different languages (DE, EN, IT, ES, FR).



## Simple handling

The SOLIVIA 20 TL inverters have an integrated DC disconnecter that saves our customers installation costs and the cost of an external DC disconnecter.

INPUT (DC)	
Max. recommended PV power	25.0 kW
Nominal power	22.0 kW
Nominal voltage	630 V
Voltage range	200 ... 1000 V
MPP range	350 ... 800 V
No. of MPP trackers	2
Max. current	60 A (30 A x 2)

OUTPUT (AC)	
Max power	21.0 kW
Nominal power	20.0 kW
Voltage range (3 phase, 3 wire)*	3 x 400 V (-20 % / +20 %)
Nominal current	29 A
Max. current	30 A
Nominal frequency	50 / 60 Hz
Frequency range *	50 Hz: 47.0 ... 53.0 Hz 60 Hz: 57.0 ... 63.0 Hz
Power factor	> 0.99 @ nominal power

GENERAL SPECIFICATION	
Model name	SOLIVIA 20 EU G3 TL
Max. efficiency	98.1 %
Efficiency EU	> 97.5 %
Operating temperature	-20 ... +60 °C
Storage temperature	-20 ... +80 °C
Humidity	0 ... 90 %

STANDARDS	
Protection degree	IP54 / IP65
Safety class	1
Configurable trip parameters	Yes
Insulation monitoring	Yes
Anti-islanding protection	VDE 0126-1-1; RD 1663; DK 5940 Ed. 2.2;
	EN 50438

MECHANICAL DESIGN	
Size (L x W x D)	952.0 x 624.7 x 278 mm
Weight	65.0 kg
Cooling	Fan
AC connector	Wieland RST50i5
DC connector	4 pairs Multicontact MC4
Communication	2 RJ45 / RS485
Display	Black/white graphical LCD
DC disconnecter	Integrated

DIRECTIVES	
EMC	EN61000-6-2; EN61000-6-3 EN61000-3-11; EN61000-3-12
Safety	EN60950-1; EN50178; IEC62103; IEC62109-1 / -2

\* AC voltage and frequency range will be programmed according to the individual country requirements. AC output is Delta grid without neutral.

Delta Energy Systems (Germany) GmbH

Tscheulinstrasse 21

D-79331 Teningen

Germany

Email: [sales@solar-inverter.com](mailto:sales@solar-inverter.com)

Sales Hotline: 0180 10 SOLAR (76527)

Mondays to Fridays from 8 am to 5 pm (apart from official Bank Holidays) (3,9 ct/min)

[www.solar-inverter.com](http://www.solar-inverter.com)

[www.secondlife.solar-inverter.com](http://www.secondlife.solar-inverter.com)

12 March 2010

